

ExxonMobil

The Mobil range of agricultural lubricants

Energy lives here™



Mobil Delvac™

Performance by **ExxonMobil**

Mobil lubricants proven both in the laboratory and in the field



Mobil has been a global specialist in lubrication for more than a century. It is a global brand, which is now present in almost two hundred countries across the globe, and is associated with strong values such as performance, innovation and expertise.

Lubrication plays a critical role in the proper maintenance of agricultural machinery, such as tractors and combine harvesters. Maintaining equipment in a perfect operating state is essential for being able to obtain your production objectives – in other words, for the efficient running of your farm. This is why Mobil lubricants are designed to provide the high level of protection that is indispensable for all of your equipment. They can help improve the productivity and efficiency of your agricultural machinery.

Proven performance in agriculture thanks to advanced technology

Mobil lubricants have been proven, both in the laboratory and in the field. They can help you to improve the reliability and usability of your machinery, optimise the performance of your agricultural equipment and reduce your operating costs. For farmers and agricultural contractors, the high performance of the lubricants translates into numerous potential advantages: helping to improve machinery performance, reduce maintenance costs, potentially extending oil change intervals¹ and the protection of equipment over the long term, which result in optimum conservation of the capital invested in operating equipment. In summary, Mobil lubricants contribute to the optimum management of your agricultural equipment. Their outstanding performance is the result of extensive practical experience in the service of the agricultural sector.

The Mobil range of lubricants meets the needs of the main agricultural applications

Agricultural machinery, including tractors and combine harvesters, are developing constantly and require the use of more advanced lubricants. This is why Mobil is constantly developing products, oils or greases that meet or even exceed the main technical requirements of the manufacturers of agricultural equipment. The result is a comprehensive range of products that meets the requirements of the main agricultural applications. This range comprises lubricants for specific applications as well as multi-purpose oils.

¹Always consult OEM manuals for proper recommendation and oil drain interval which may depend on, for example, make, model, local variations, fuel S, operating conditions.

Our experts are at your disposal, ready to provide you with advice and to answer any of your questions. For more information, please visit www.mobildelvac.co.uk

High-performance oils for diesel engines

Mobil Delvac 1 LE 5W-30

Fully synthetic heavy-duty diesel engine oil

Meets or exceeds the requirements of:	Builder Approvals
ACEA E9 / E7 / E6	MB-Approval 235.28 / 228.51 / 228.31
API CJ-4 / CI-4 PLUS / CI-4 / SN	MAN M 3677 / 3477 / 3271-1
JASO DH-2	Volvo VDS-4 / VDS-3
Caterpillar ECF-3	Voith Retarder Oil Class B
Cummins CES 20081	Deutz DQC IV-10 LA
DAF Extended Drain	Detroit Fluids Specification 93K218
Ford WSS-M2C171-E	Mack EO-O Premium Plus
	MTU Oil Category 3.1
	Renault Truck RLD-3 / RLD-2
	Scania Low Ash
	Avtodisel YaMZ-6-12
Recommended by ExxonMobil for use in applications	
Renault Truck RGD / RXD	

Mobil Delvac MX ESP 10W-30

Extra high performance diesel engine oil

Meets or exceeds the requirements of:	Builder Approvals
API CJ-4 / CI-4 PLUS / CI-4 / CH-4 / SM	Volvo VDS-4 / VDS-3
ACEA E9 / E7	MB-Approval 228.31
Caterpillar ECF-3	Deutz DQC II-10 LA
JASO DH-2	MAN M 3575
Cummins CES 20081	Mack EO-O Premium Plus
	Renault Trucks RLD-3
Recommended by ExxonMobil for use in applications	
API CG-4 / CF	

Mobil Delvac MX ESP 15W-40

Extra high performance engine oil

Meets or exceeds the requirements of:	Builder Approvals
API CJ-4 / CI-4 PLUS / CI-4 / CH-4 / SM / SL	Detroit Fluids Specifications 93K218 / 93K214
ACEA E7/ E9	Mack EO-N Premium Plus 03 / Mack EO-O Premium Plus
Caterpillar ECF-3	MAN M3575
JASO DH-2	Deutz DQC II-10 LA
Cummins CES 20081	MB-Approval 228.31
	Volvo VDS-4 / VDS-3 / VDS-2
	Allison TES-439
	Renault Trucks RLD-3
Recommended by ExxonMobil for use in applications	
API CG-4 / CF-4 / CF-2 / CF	
MAN M 3275-1	
Allison C-4	

High-performance oils for diesel engines

Mobil Delvac XHP ESP 10W-40

Emission system protection diesel engine oil

Meets or exceeds the requirements of:	Builder Approvals
ACEA E9 / E7 / E6 / E4 API CJ-4 / CI-4 Plus / CI-4 JASO DH-2 DAF Extended Drain Cummins CES 20081 CAT ECF-3 Isuzu DEO (w/DPD Equipped Vehicles)	MB-Approval 228.51 / 235.28 MAN M 3477 / M 3575 / M 3271-1 MTU Oil Category 3.1 Volvo VDS-4 / VDS-3 Renault Truck RLD-3 / RLD-2 Deutz DQC IV-10 LA Scania Low Ash Voith Retarder Oil Class B Kamaz Euro-3,-4 & -5 engines Avtodisel YaMZ-6-12
Recommended by ExxonMobil for use in applications	
Renault Truck RXD / RGD	

Mobil Delvac MX 15W-40

Extra high performance diesel engine oil

Meets or exceeds the requirements of:	Builder Approvals
API CI-4 / CH-4 / SL / SJ ACEA E7 Caterpillar ECF-2 Cummins CES 20077 / 20076 Isuzu DEO (w/o DPD Equipped Vehicles)	MB-Approval 228.3 Mack EO-M PLUS / EO-N Volvo VDS-3 MAN M 3275-1 Renault Trucks RLD-2 MTU Oil Category 2 Kamaz Euro-3,-4 & -5 engines Avtodisel YaMZ-6-12
Recommended by ExxonMobil for use in applications	
API CG-4 / CF-4 / CF ACEA A2 / B2 Volvo VDS-2 Renault Trucks RLD	Mack EO-M Cummins CES 20072 / 20071 Detroit 7SE 270 (4-Stroke Cycle)

Multi-purpose tractor oils

Mobilfluid 426

Extra high performance multipurpose tractor fluid

Meets or exceeds the requirements of:	Builder Approvals
Kubota UDT ASTM D6973 (Eaton 35VQ)	Volvo WB 101 ZF-TE-ML 03E / 05F / 06K / 17E / 21F
Recommended by ExxonMobil for use in applications	
API GL-4 AGCO Powerfluid 821 XL Allison C-4 (Agriculture Applications Only) Caterpillar TO-2 CNH MAT 3505 / MAT 3525 Denison UTTO / THF	FNHA-2-C-201.00 Ford ESN-M2C-134-D J. I. Case MS 1204-07 / 09 John Deere J20C Massey Ferguson M-1145 / M-1143 / M-1141 / M-1135

Mobil Agri Extra 10W-40

Super tractor oil universal (STOU) lubricant

Builder Approvals	Recommended by ExxonMobil for use applications
Massey Fergusson M-1145 ZF TE-ML 06C / 07B	API CE / SF API GL-4 Allison C-4 (Agriculture Applications Only) Massey Fergusson M-1144 / M-1139 John Deere J27 Ford M2C 159B

Mobilfluid LT

Extra high performance multipurpose tractor fluid

Recommended by ExxonMobil for use in applications	
Caterpillar TO-2 Denison HF-0 / HF-1 / HF-2 (Pumps Only)	John Deere J20D Vickers 35VQ25A

High-performance multi-purpose greases

Mobilgrease Special

High performance multi-purpose automotive grease

- Provides equipment protection and extended life under severe operating conditions
- Extra protection against rust and corrosion for reduced maintenance and downtime
- Good resistance to water washout ensures proper lubrication even in the presence of water contamination
- Good pumpability in centralised systems

Mobilgrease XHP 322 Mine

Extra heavy-duty off-highway and mining lubricant

- Excellent EP and anti-wear properties
- Optimum equipment protection with extended re-lubrication intervals
- Exceptional resistance to water washout and spray-off
- Excellent low temperature pumpability and start-up performance

Mobilgrease XHP 222

Extra heavy-duty off-highway and mining lubricant

Meets or exceeds the requirements of:	Builder Approvals
DIN 51825: (2004-06) KP2N-20	Fives Cincinnati P-64

Mobilux EP 2

High performance industrial grease

Meets or exceeds the requirements of:
DIN 51825 KP2K-20

Hydraulic oils: Designed to perform under demanding conditions

Mobil DTE 10 Excel 46

Premium quality hydraulic oil

Meets or exceeds the requirements of:	Builder Approvals
DIN 51524-2: 2006-09	Denison HF-0
DIN 51524-3: 2006-09	Eaton Vickers 694 (encompasses former I-286-S, M-2950-S or M-2952-S)
ISO 11158 L-HV	Frank Mohn, Framo hydraulic cargo pumping
JCMAS HK VG46W (JCMAS P 041:2004)	Fives Cincinnati P-70
Bosch-Rexroth RE 90220-01	ORTLINGHAUS-WERKE GMBH ON 9.2.10
Arburg	
Krauss-Maffei Kunststofftechnik	
HOCNF Norway/NEMS	

Mobil DTE 10 Excel 68

Premium quality hydraulic oil

Meets or exceeds the requirements of:	Builder Approvals
DIN 51524-2: 2006-09	Denison HF-0
DIN 51524-3: 2006-09	Eaton Vickers 694 (encompasses former I-286-S, M-2950-S or M-2952-S)
ISO 11158 L-HV	Fives Cincinnati P-69
Bosch-Rexroth RE 90220-01	ORTLINGHAUS-WERKE GMBH ON 9.2.10
Voith VN108 4.3.3	STROMAG AG TM-000 327
HOCNF Norway/NEMS	

Univis N 32 & 46 & 68

Hydraulic oil

Meets or exceeds the requirements of:	Recommended by ExxonMobil for use
DIN 51524-3 2006-9	Denison HF-0 / HF-1 / HF-2
ISO L-HV (ISO 11158, 1997)	Eaton I-286-S
	Eaton M-2950-S

Mobil SHC Hydraulic Oil EAL 32 & 46

Premium quality high performance hydraulic oil

Meets or exceeds the requirements of:	Builder Approvals
ISO L-HEES, (ISO 15380, 2011)	RAL – Blue Angel (RAL-UZ 79)
Swedish Standard SS 15 54 34 AAV (2015)	ECO Label – Hydraulic Oil
WGK –Non Water Hazardous	

Oils for gearboxes, powered axles and final reduction gears

Mobilube 1 SHC 75W-90

Fully synthetic automotive gear lubricant

Meets or exceeds the requirements of:	Builder Approvals
API GL-5 / MT-1	JSC AVTODIZEL YaMZ Gearboxes
ZF TE-ML 07A / 08	MAN 341 Typ E3 / Typ Z2
Scania STO 1.0	MAN 342 Typ M3 / S1
BOSCH TE-ML 08	MB-Approval 235.8
	ZF TE-ML 02B / 05B / 12L / 12N / 16F / 17B / 19C/ 21B
	SAE J2360
	Komatsu Part 195-32-61990-04
Recommended by ExxonMobil for use in applications	
API GL-4	

Mobilube GX –A 80W

Automotive gear lubricant

Meets or exceeds the requirements of:	Builder Approvals
ZF TE-ML 08	MB-Approval 235.1
BOSCH TE-ML 08	MAN 341 Typ E1 / Typ Z2
	ZF TE-ML 17A
Recommended by ExxonMobil for use in applications	
API GL-4	
MAN 341 Typ Z1	

Mobilube HD 80W-90

Heavy duty automotive gear lubricant

Meets or exceeds the requirements of:
API GL-5

Mobilube LS 85W-90

Limited-slip gear lubricant

Meets or exceeds the requirements of:
API GL-5
ZF TE-ML 05C / 12C / 16E / 21C



ExxonMobil Fuels & Lubricants
(Insert local entity address)

©2015 Exxon Mobil Corporation
Exxon, Mobil, Esso and the ExxonMobil logotype are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries. MobilServ is a service mark of Exxon Mobil Corporation or one of its subsidiaries. The term "ExxonMobil" is used for convenience only and could refer to Exxon Mobil Corporation or one of its affiliates as the case may be. Other logotypes and trademarks are the property of the respective owners.

For more information visit us at www.mobildelvac.com

Product information correct at the time of publication.

Mobil™ products described in this document are also available from your authorised distributor at the following address:

Distributor's stamp

A large, empty white rectangular box with rounded corners, intended for a distributor's stamp.